


















MAX21 WORM

MODEL	축배치 및 회전방향	도면		
 <p>WU-60 W ≈ 10kg</p>				
 <p>WB-60 W ≈ 10kg</p>				
 <p>WV-60 W ≈ 10kg</p>				

II-2

전동능력표

수치는 1일 8~10시간 연속 운전이고 균일 하중의 수치입니다.

RATIO	1800				1500				1200			
	INPUT HP	OUTPUT HP	OUTPUT T kgf-m	OUTPUT O.H.L kgf	INPUT HP	OUTPUT HP	OUTPUT T kgf-m	OUTPUT O.H.L kgf	INPUT HP	OUTPUT HP	OUTPUT T kgf-m	OUTPUT O.H.L kgf
1/10	2.32	1.87	7.44	98	2.08	1.67	7.95	104	1.88	1.47	8.8	110
1/15	1.73	1.32	7.91	116	1.55	1.19	8.46	123	1.36	1.01	9.07	133
1/20	1.21	0.89	7.15	138	1.11	0.80	7.66	146	0.98	0.69	8.31	157
1/25	1.24	0.92	9.10	153	1.12	0.83	9.70	162	0.99	0.71	10.5	174
1/30	1.15	0.75	9.31	151	1.05	0.71	10.0	159	0.92	0.59	10.6	172
1/40	0.83	0.52	8.27	178	0.75	0.47	8.83	189	0.67	0.39	9.49	200
1/50	0.77	0.49	9.70	200	0.71	0.43	10.2	200	0.63	0.37	11.0	200
1/60	0.64	0.39	9.20	200	0.59	0.35	9.70	200	0.51	0.29	10.4	200

RATIO	900				600				300			
	INPUT HP	OUTPUT HP	OUTPUT T kgf-m	OUTPUT O.H.L kgf	INPUT HP	OUTPUT HP	OUTPUT T kgf-m	OUTPUT O.H.L kgf	INPUT HP	OUTPUT HP	OUTPUT T kgf-m	OUTPUT O.H.L kgf
1/10	1.57	1.21	9.68	121	1.23	0.93	11.1	138	0.65	0.48	11.6	175
1/15	1.17	0.85	10.2	145	0.91	0.64	11.5	167	0.48	0.32	11.6	200
1/20	0.83	0.57	9.16	172	0.65	0.43	10.4	198	0.39	0.24	11.6	200
1/25	0.83	0.59	11.5	192	0.48	0.32	11.6	200	0.31	0.19	11.6	200
1/30	0.79	0.48	11.6	189	0.55	0.32	11.6	200	0.29	0.16	11.6	200
1/40	0.59	0.32	10.4	200	0.45	0.24	11.6	200	0.25	0.12	11.6	200
1/50	0.40	0.23	9.22	200	0.31	0.17	10.3	200	0.19	0.11	11.6	200
1/60	0.43	0.24	11.3	200	0.25	0.12	9.52	200	0.15	0.07	11.2	200